












COMPARISON OF PRODUCT FEATURES

| U-Phone-iT | Regal Pro | Regal Pro-Max | Features: |
|---|--|---|--|
| 10 AMP | 15 AMP | 20 AMP | Main circuit protection |
| 1000 Watts | 1700 Watts | 2400 Watts | Possible switching power outlet 1 |
| 1000 Watts | 1700 Watts | 1400 Watts | Possible switching power outlet 2 |
| 1000 Watts | 1700 Watts | 2400 Watts | Total available unit switching power (outlet 1 plus outlet 2) |
| 5-15R  | 5-15R  | 5-15R or 5-20R  | Unit outlet/receptacle accepted NEMA format |
| 5-15P  | 5-15P  | 5-20P  | Power inlet plug NEMA format (Adaptor P6050 available to convert to NEMA 5-15 to 5-20 but lowers to 1700 watts, 15 amps available on unit.) |
| Y | Y | Y | Pay-as-You-Go cell service account on the AT&T 4G GSM. |
| Y | Y | Y | Available CMS service for \$80.00 for 360 days of service |
| Y | Y | Y | Security - Authorized user list for phone call activation |
| Y | Y | Y | Security - Password protection for text messaging |
| Y | Y | Y | Master Power LED indicator. |
| Y | Y | Y | Unit is delivered with an active phone number and at least 80 days of cell service and \$8.00 of Air time on "AirVoice Wireless" |
| Y | Y | Y | Complementary setup of "AirVoice Wireless" web account |
| Y | Y | Y | Ready to use out of the box. |
| Y | Y | Y | Power restorations confirmed by text message to admin(s). |
| Y | Y | Y | Individual outlet activation control. <i>On/Off, timer controlled,</i> |
| Y | Y | Y | Programable phone activation |
| Y | Y | Y | Text based control |
|  |  |  | iOS app for message formatting |
| Can be used with Regal app with limitations |  |  | Android app for message formatting |
| N | Y | Y | Clock operations (Activate a specific time of day for specific length of time) |
| Plastic | Metal | Metal | Main case material |
| Y | Y | N | Available through Aircraft Spruce |
| N | Y | Y | Available through Preheatremote.com |
| 100 - 130 VAC | 100 - 130 VAC | 100 - 130 VAC | Voltage range of operation |
| Y | Y | Y | Available external antenna. (Part number: P6043) |
| P6040 | P6041 | P6042 | Part number |